RDC+

REFCON manual data handling device

- Large full VGA Color touch screen display
- Microsoft Windows Mobile based software for graphical representation of data.
- Connection to REFCON PC via standard USB connection
- Fast transfer of container data between PC and handheld device
- Function keys for easy access to primary functions
- Rechargeable battery included (Recharged through docking station)

Description

With your REFCON reefer container monitoring system connected to the load calculator or terminal planner, the task of collecting data from the non-communicating containers becomes very simple:

- Transfer the basic reefer container information from the load calculator or terminal planner to REFCON, including container ID, location, expected temperature setpoints, etc.
- Transfer a list of all non-communicating containers from the REFCON system to the handheld RDC+ unit
- Go to the containers and check the listed data with the actual data on the containers
- Accept or change the data in the RDC+
- Go back to the REFCON system and load the corrected data into the system, using a cradle or cable connection

You will now have the actual container data available in the REFCON system. You will also have the alarms on your screen, and you will be able to make the same reports and printouts as for the communicating containers.



Applications

Documentation from non-communicating reefer containers (without modem installed) on REFCON systems



Environmental Specifications:

| Operating temperature | -10°C < T _{op} < 50°C |
|-----------------------|---|
| Ingress Protection | IP 65 |
| Shock | 26 drops of 5 ft. (1.5 meters) to polished concrete |
| Humidity | 5-95% RH non-condensing |

Physical dimensions:

| Length | 190 mm |
|-----------------------|--------|
| Width | 98 mm |
| Height | 44 mm |
| Weight (with battery) | 491 g |

Electrical specification:

| Power supply | Auto-ranging: AC 100 - 240 V, 50/60 Hz |
|---------------------------------|--|
| Rechargeable battery (included) | 3,7 V, 3000 mAh |

Accessories:

| Controller retriever cable for old type Daikin units | P/N 5062-005 |
|--|--------------|
| USB tether cable | P/N 1189-155 |
| Protective Carrying Case | P/N 1189-154 |
| Spare 3Ah Battery | P/N 1189-156 |

LogMann II (P/N 1189-004) - Included items:

| Hand Held device (PSION Workabout Pro S 3G) with 256 MB storage capacity |
|--|
| LogMan II software installed |
| Hand strap |
| Rechargeable battery |
| Getting started user instruction |
| Docking Station |
| USB Cable (1,5 meter) |
| Controller retriever cable |
| |

Emerson Climate Technologies - Transportation Solutions - $Denmark \cdot Phone + 45\ 70\ 23\ 44\ 44 \cdot ts.support@emerson.com$

Climate.Emerson.com